

DATA SHEET

Receptacle connector



Part Number

6061.SMA.JST.00.111

Description

SMA, Jack, Straight, PCB Mount

Interface Standard

IEC 60169-15

Suitable Cable

N/A



Electrical Data

Impedance	50	Ω
Max. operating frequency	18	GHz
Insulation resistance	≥ 5000	$M\Omega$
Center contact resistance	≤ 3	$m\Omega$
Outer contact resistance	≤ 2.5	$m\Omega$
Dielectric withstanding voltage	≥ 1000	Vrms @ 50Hz
Working voltage	≥ 480	Vrms @ 50Hz

Mechanical Data

Mating cycles	≥ 500	
coupling recommended toque	$\geq 0.8 \sim 1.1$	Nm
coupling proof torque	≥ 1.7	Nm
coupling nut tensile strength	≥ 270	N
Center contact axial force	≥ 27	N
Center contact axial torque	≥ 0.03	Nm
contact gauge ret. Force	≥ 0.28	N

Environmental Data

Operating temperature	-55~155°C	connector limited
2002/95/EC (ROHS)	compliant	
Sealing	N/A	
Thermal shock	MIL-STD-202 Method107, condition B	
Moisture resistance	MIL-STD-202 Method106	
Corrosion resistance	MIL-STD-202 Method101, condition B	
Vibration	MIL-STD-202 Method204, condition D	
Shock	MIL-STD-202 Method213, condition I	

Material Data

Piece Parts	Material	Surface Plating
center contact	Beryllium copper	Au
body	Brass	Au
insulator	PTFE	
lock washer	Phosphor bronze	Au
nut	Brass	Au

Zeeteq the technoledge connecting people

No. 51 Sci.-Tech Industry Park, Huoju
Road, SND, Suzhou, China
Zip: 215009

Tel: +86 512 6807 8808
Fax: +86 512 6807 8818
www.zeeteq.com

Rev.: a
issued: 2008-5-23
page: 1 of 1