

DATA SHEET

Cable connector



Part Number

5008.SMA.PRC.02.111

Description

SMA, Plug, Straight, Cable Mount

Interface Standard

IEC 60169-15

Suitable Cable

RG405/U, UT86



Electrical Data

Impedance	50	Ω		
Max. operating frequency	18	GHz	connector limited	
Frequency range	DC to 1GHz	1 to 2.2GHz	2.2 to 3GHz	3 to 6GHz
VSWR	≤1.02	≤1.02	≤1.06	≤1.15
Insertion loss	0.05 $\sqrt{f(\text{GHz})}$	dB		
Insulation resistance	≥5000	MΩ		
Center contact resistance	≤3	mΩ		
Outer contact resistance	≤2.5	mΩ		
Dielectric withstanding voltage	≥1000	Vrms @ 50Hz	cable limited	
Working voltage	≤250	Vrms @ 50Hz	cable limited	

Mechanical Data

Mating cycles	≥500	
Center contact axial force	≥22	N
Center contact axial torque	≥0.03	Nm
contact gauge ret. Force	≥0.28	N
Center contact	solder	
Outer contact	solder	
Cable retention force		
-RG405/U	≥100	N
-UT86	≥158.5	N

Environmental Data

Operating temperature	restricted by cable and/or silicone used
2002/95/EC (ROHS)	compliant
Sealing	N/A
Thermal shock	MIL-STD-202 Method107, condition B
Moisture resistance	MIL-STD-202 Method106
Corrosion resistance	MIL-STD-202 Method101, condition B
Vibration	MIL-STD-202 Method204, condition D
Shock	MIL-STD-202 Method213, condition I

Material Data

<u>Piece Parts</u>	<u>Material</u>	<u>Surface Plating</u>
center contact	Brass	Au
body	Brass	Au
insulator	PTFE	
nut	Brass	Au
O-ring	silicone rubber	
spring ring	Stainless steel	

Zeeteq the technoledge connecting people
 No. 51 Sci.-Tech Industry Park, Huoju
 Road, SND, Suzhou, China
 Zip: 215009

Tel: +86 512 6807 8808
 Fax: +86 512 6807 8818
www.zeeteq.com

Rev.: a
 iussed: 2008-5-9
 page: 1 of 1