

DATA SHEET

Cable connector



Part Number

5035.N.PSC.02.133

Description

N, Plug, Straight, Cable Mount

Interface Standard

IEC 60169-16

Suitable Cable

RG405,UT86



Electrical Data

Impedance	50	Ω		
Max. operating frequency	18	GHz	connector limited	
Frequency range	DC to 1GHz	1 to 2.2GHz	2.2 to 3GHz	3 to 6GHz
VSWR	≤ 1.03	≤ 1.04	≤ 1.05	≤ 1.12
Insertion loss	$0.03 \sqrt{f(\text{GHz})}$	dB		
Insulation resistance	≥ 5000	M Ω		
Center contact resistance	≤ 1	m Ω		
Outer contact resistance	≤ 0.25	m Ω		
Dielectric withstanding voltage	≥ 1000	Vrms @ 50Hz	cable limited	
Working voltage	≤ 400	Vrms @ 50Hz	cable limited	

Mechanical Data

Mating cycles	≥ 500	
Center contact axial force	≥ 28	N
Center contact axial torque	≥ 0.03	Nm
contact gauge ret. Force	≥ 0.56	N
Center contact	solder	
Outer contact	solder	
Cable retention force		
-RG405	≥ 100	N
-Ut86	≥ 158.5	N

Environmental Data

Operating temperature	restricted by cable and/or silicone used
2002/95/EC (ROHS)	compliant
Sealing	N/A
Thermal shock	MIL-STD-202 Method107, condition B
Moisture resistance	MIL-STD-202 Method106
Corrosion resistance	MIL-STD-202 Method101, condition B
Vibration	MIL-STD-202 Method204, condition D
Shock	MIL-STD-202 Method213, condition I

Material Data

Piece Parts	Material	Surface Plating
center contact	Brass	Au
body	Brass	CuSnZn
insulator	PTFE	
nut	Brass	CuSnZn
spring ring	Phosphor bronze	
gasket	silicone rubber	

Zeeteq the technoledge connecting people
 No. 51 Sci.-Tech Industry Park, Huoju
 Road, SND, Suzhou, China
 Zip: 215009

Tel: +86 512 6807 8808
 Fax: +86 512 6807 8818
www.zeeteq.com

Rev.: a
 issued: 2008-5-20
 page: 1 of 1